



*MS RAILING IS INDICATIVE ONLY,
TO BE FINALISED AS PER SITE



GENERAL NOTES:

1. ALL DIMENSIONS & LEVEL ARE IN MM UNLESS STATED OTHERWISE.
2. I.G.C. CORRESPONDS TO 0.00M, THE F.O.L OF THE BUILDING SHALL BE AS SHOWN ON THE DRAWING.
3. 1000 MM DIA. ROLLING PLUMBER SHALL BE PROVIDED ALONG THE BUILDING WHEREVER POSSIBLE.
4. ROLLING PLUMBER OVER A DOOR SHALL BE 750MM & ROLLING SHUTTER SHALL BE 1500MM.
5. FOR ROLLING PLUMBER DETAIL REFER SEPARATE DRAWING.
6. SIZES OF COULUMBS ARE JUST INDICATIVE, SIZES SHALL BE AS PER STRUCTURAL DRAWING.
7. FLOOR PERFORMER CRAN SHALL BE 1500.
8. WALLS SHALL BE OF BRICK (3/4BRS) OR MASONRY OF SIZE 230MM THK. FOR EXTERNAL WALLS & INTERNAL WALLS. WHEREVER INDICATED THE INTERIOR WALLS SHALL BE OF 150MM THK. CONCRETE OR 150MM THK OF 150mm THK OF 150mm THK OF CONCRETE GRADE M20.
9. ALL DIMENSIONS SHALL BE IN METERS.
10. LOCATION/ORIENTATION/COORDINATES OF THE BUILDING SHALL BE CROSS-CHECKED WITH STRUCTURAL/CIVIL DRAWINGS. IN CASE OF ANY MID-MATCH THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE START OF CONSTRUCTION.
11. PLUMB BEAM LEVEL, SIZE & LOCATION SHALL BE AS PER STRUCTURE.
12. INDICATIVE SIZES OF DOORS, STAIRS & BALCONY IS INDICATIVE ONLY. TO BE FINALISED AS PER SITE.

LEGENDS

- FFL-FINISHED FLOOR LEVEL
F.G.L.-FINISHED GROUND LEVEL
T.O.C -TOP OF CONCRETE
R.S - ROLLING SHUTTER
W-WINDOW
D-DOOR
V-VENTILATOR
R.W.P -RAIN WATER PIPE
R.W.O -RAIN WATER OUTLET
 BRICK WALL
 R.C.C



* GROUND TO TILL ROOF RISER = 150 mm



PART DETAIL OF
RAILING
SCALE- 1: 25



14-08-2000
Assistant Engineer (Civil)
BSPTCL

14.8
Executive Engineer (Civil)
B.S.P.T.C.L

Drawing is approved
subject to overall
responsibility of the contractor
in terms of contract agreement
or, turn key for the work

[Signature]
17.8.20
Chief Engineer, (Civil)
BSPCL

Superintending Engineer (Civil)
BSPCT

Bihar State Power
Transmission Company
Limited (BSPTCL)

Title: ARCHITECTURAL STAIRCASE DETAIL FOR 3BHK APARTMENT

Drg.No.: - CD_3BHK21- 06

Scale:
AS PER SHOWN

Sheet:
01 OF 01